


GP-T8693

Pre-Connectorized Indoor Fiber Optic Rosette with Cable




Application

- The Fiber Optic Rosette is designed for FTTH applications in indoor environments. It enables efficient drop cable and indoor cable connections for seamless network integration.
- The rosette supports indoor cable storage and distribution to optimize space and organization.

Key Features

- The rosette features a small size and light weight for convenient handling and installation.
- It is constructed from ABS material that provides fireproof and dust-proof protection.
- The radian appearance makes it slinky and aesthetically suitable for modern interiors.
- The design accommodates various modules and multimedia interfaces for versatile use.
- The track rail ensures effective management of fiber optic cables within the unit.



Dimension Drawing



Specifications

Part No.	GP-T8693
Dimensions	93 × 83 × 16.5 mm
Material	ABS (UL94 V0 Optional)
Color	White (Customizable)
Mounting	Wall Mount
IP Rating	IP20
Fiber Type	G.652A2, G.657B3
Fiber Color	Natural
Cable Type	0.9 mm tight buffer
Cable Color	Natural
Connector Type	SC / LC
End Face	APC / UPC
Cable Weight	Approx. 0.7kg/km
Min. Bending Radius	15 mm (Static) / 30 mm (Dynamic)
Attenuation (dB/km)	≤ 0.4 dB/km @ 1310 nm ≤ 0.3 dB/km @ 1550 nm
Insertion Loss (IL)	≤ 0.3 dB
Return Loss (RL)	UPC ≥ 50 dB APC ≥ 55 dB
Operating Temperature	-40°C to +70°C

Accessories

Picture	Name	Size	Quantity
	Wall-mounting Kit	/	2 Pairs
	Double-sided Adhesive Tape	93 × 83 mm	1 PC

Ordering Information

Part No.	Description
GP-T8693-1A-1PC15	1 × Adapter, 1 × 15 m Patch Cord, 4 sets of Clip Holders (100 pcs total)
GP-T8693-1A-1PC20	1 × Adapter, 1 × 25 m Patch Cord, 4 sets of Clip Holders (100 pcs total)

◆ Other configurations are available upon request. Customization supported.

Packing List

Part No.	PCS / CTN	G.W. / CTN	Carton Size
GP-T8693	200	25 KG	50 × 50 × 36 CM